

Series 3

MR52

SERIES I/O DUAL CARD READER INTERFACE

The new Authentic Mercury MR Series 3 Serial Input/Output (SIO) modules enable system expansion of Authentic Mercury intelligent controllers as part of Mercury's distributed architecture. The enhanced modules offer an improved processor and increased memory, plus feature an embedded crypto memory chip that provides a secured layer of encryption to onboard sensitive data. Built on the Authentic Mercury open platform, Series 3 modules provide the necessary flexibility for OEMs, channel partners and end customers to choose the controller configuration that best fits their needs.

The MR52 Series 3 is a dual card reader interface panel with on-board flexibility to connect a wide range of security devices. The MR52 is easy to install and provides the required I/O for interfacing two card readers, eight general-purpose input monitor points and six control relays to any Authentic Mercury series intelligent controller.

With two-wire RS-485 connectivity, the MR52's two reader ports support OSDP, OSDP Secure Channel, FICAM government profiles, keypads, biometric readers, Wiegand, clock and data, magnetic stripe, F/2F and supervised F/2F reader technologies. System configuration and setup are provided through Mercury OEM partner software applications.

The MR52 Series 3 is the latest generation door interface module for Authentic Mercury intelligent controllers, the platform of choice for customers seeking open architecture access control solutions.

Open Architecture

High performance, reliable platform enables use of hardware with Mercury OEM partners software solutions

OSDP Protocol:

Supports OSDP and Secure Channel protocol for device connectivity, file transfer and extended applications such as biometrics and federal government profile support

Enhanced Security

Embedded crypto memory chip provides secured layer of encryption to protect sensitive data

Versatile Interoperability

Same reliable interface and identical footprint as the Series 2 Mercury IO modules, enabling seamless upgrades for existing deployments

FEATURES:

- AES 128/256 bit data encryption
- HSPD-12/FIPS201 compliant
- UL 294 recognized, CE compliant, FCC, RoHS
- Supports OSDP, OSDP Secure Channel, FICAM government profiles, keypads, biometric readers, Wiegand, clock and data, magnetic stripe, F/2F and supervised F/2F reader technologies
- RS-485 host connectivity

Application Notes


The inputs and the relays may be assigned to door-related functions or to general-purpose I/O. The inputs support normally open, normally closed, supervised, and non-supervised circuits. End-of-line (EOL) resistance values are configurable, and the relays can be configured for fail-safe or fail-secure operation.

When connected to an Authentic Mercury intelligent controller, the MR52 can relate the activities of selected system devices to other devices within the system, generating actions and allowing activities to occur independent of the host. The MR52 can also locally process access requests based on facility code verification, even when disconnected from an intelligent controller. Up to eight facility codes may be active in each MR52.

***Note:** Up to two entry/exit door applications (4 readers total) can be supported when connected to OSDP readers.

SERIES 3 MR52 SPECIFICATIONS

Primary Power	12-24 Vdc +/- 10%, 550mA maximum
Host Communication	Host RS-485, 2-wire, 4,000' (twisted pair with shield, Belden 9841)
Reader Ports	2 Reader Ports*
Card/Keypad Data	OSDP, Clock/Data, Data-1/Data-0, RS-485, or F/2F
Keypad	8-bit Mercury, 8-bit Dorado/HID, 4-bit HID
Reader Power	Pass-through or 12 Vdc regulated 300mA each reader
LED	One-wire bi-color LED or two-wire LED
Buzzer	Only with 'one-wire' LED
Inputs	8 General Purpose: Programmable circuit type 2 Dedicated: Tamper and Power Monitor
Outputs Relays	Six Form-C Relays: Normally open contact (NO): 5A @ 30 Vdc resistive Normally closed contact (NC): 3A @ 30 Vdc resistive
Dimensions	6.0" W x 8.0" L x 1.0" H (152mm W x 203mm L x 25mm H)
Temperature	0-70 °C operational, -55-85 °C storage
Humidity	5 to 95% RHNC
Standards	UL 294 recognized, CE compliant, RoHS, FCC Part 15 Subpart B



The Authentic Mercury open platform delivers quality assurance derived from the most proven and reliable hardware in the industry. Driven by engineering excellence and technology leadership, Authentic Mercury hardware is designed as an access control platform that easily encompasses emerging technologies, changing industry standards and evolving system environments.

